ADTRAXION Am Player

Compact sized Adtraxion Player, providing great performance



The Adtraxion Am Player is a robust and reliable digital signage player. It is characterized by its superior graphics performance and a rich combination of video output interfaces.

Ideal for users that need industrial strength for the most demanding digital signage installations.

Main benefits

- > 24/7 operation
- > Robust and reliable
- > Standard 4 Year warranty
- > Full HD playback
- > Low power consumption
- > Compact, low-profile design
- > Supports many content formats
- > Wi-Fi

Adtraxion Am Player



Watchdog

For reliable operation, the watchdog functionality is designed in both the hardware and the software configuration, to secure 24/7 operation.

Monitoring

The player has an extensive monitoring on board. Its status, temperature, load and memory usage can be remotely monitored.

High level of network security

To prevent unauthorized network activities different levels of security are implemented. The dedicated firewall settings will prevent unauthorized network access. With its encrypted communication and propriety protocol, the Adtraxion Am Player is even more safe and secure.

Mechanical		Supported Media F	ormats
Dimensions	220 x 44.2 x 150 mm	Video formats	offices
Weight	1.7 kg	MPG	MPEG layer 1,2 (MP@HL - max. 25 Mbps)
Weight		WMV	WMV9/VC-1 - MP@HL (max. 18 Mbps)
Environment		MP4	H264/AVC - HP@L4.0/4.1 (max. 15 Mbps)
Operating Temperature	0 ~ 40° C		
Storage Temperature	-20 ~ 70° C	Audio formats	
Relative Humidity	95% @ 40° C (non-condensing)	MP3	MPEG-1 Audio Layer II
· ·		WAV	PCM 44KHz, 16-bit (stereo)
Power		WMA	WMA 9 (stereo)
Pwr. Con. Input Voltage	Average 18W, Maximum 30W	AC3	Dolby Digital (2.0, 2.1 and 5.1)
		MP4	AAC-LC (stereo)
Display			
Output	HDMI x 1, DVI-D x 1, VGA x 2	Image formats	
		JPG	JPEG (RGB)*
I/O Interface		BMP	Windows Bitmap (RGB, RGBA, RLE)*
HDMI	Yes	GIF	Graphics Interchange Format*
DVI-D	Yes	PNG	Portable Network Graphics (RGB, RGBA)*
VGA	Yes		
Audio	2 audio phone jacks for Line-Out, Mic-in	Animation formats	
Serial Ports	2 x RS-232	SWF	Flash 10
USB Interface	4 x USB ports, USB 2.0 Compliant	PPTX	PowerPoint 2010
Lan	2 (RJ-45) 10/100/1000 Mbps	WEB	Microsoft Silverlight 5
	One port is reserved for management with		
	Fixed IP Address	Streaming formats	
		UDP SPTS	MPEG-2 (SD) (max. 8Mbit/sec)
Peripheral		A 65 (110)	H264/AVC1 (HP@L4.0/4.1) (max. 10 Mbit/sec)
WiFi	WIFI 802.11 b/g/n	ASF/URL	WMV9/VC-1 TCP/UDP streaming support
		A 11	through RTSP/MMS protocol (max. 10Mbit/sec).
Storage capacity		Audio	MPEG-1 Audio Layer II
HDD capacity	160 GB HDD		AAC LC (Stereo)
Mounter			AC3 (Dolby Digital 2.0, 2.1 and 5.1)
Warranty	(Vears (aveluding maying parts)	Other formats	
Warranty	4 Years (excluding moving parts)	Other formats	Live RSS 2.0
* Image files should not exceed 1MB in file size or 1920 pixels wide by 1080 pixels tall. We			Text files (ANSI/Unicode)
strongly recommend uploading images at the size you wish for them to display on the			URL/WEB
screen.	inages at the size you wish for them to display on the		

Ordering information

ADXAM01

Adtraxion Am Player



www.adtraxion.com